


**Horizon**

# RD series

Rotary Die-cut System

**Simple, high quality,  
compact rotary Die-cut system.**




## Improve your die cutting process!

**Easy change over the simple operation. Rotary Die-cut System allows flexibility across a wide range of products.**

### Features

---

1. **Rotary Die-cut System** - Rotary Die-cutter designed to meet the growing demand for short run product. The rotary die-cutters are light and compact compared to the normal die cutters.
2. **Flexible substrate** - Die-cut and Kiss-cut in various substrates for digital and offset printed sheets.
3. **One pass processing** - Feeding, die cutting, and separating are achieved in one pass.
4. **Save the cost of making die** - Uniquely designed servo motor controlled "Repeat Register" feature allows multiple-up applications from single-up die to minimize die cost.
5. **Simple and easy operation** - Reduces costly labor steps and increases productivity with easy setup and operation versus steel rule or mechanical dies.





## Two types of Die-cut Systems

### RD-4055

Rotary Die-cut System (Max. 400 x 550 or 15.74" x 21.65") Die-cut, Crease, Perforation, Slit, Hole punch and round corner in various substrates up to 0.5 mm or 0.019" (only for die cutting).



Sheet Feeder FFU-4055 + Rotary Die-Cutter RD-4055 + Separator SPC-4055

### RD-3346

Rotary Die-cut System (Max. 330.2 x 550 mm or 13" x 21.65") Repeat function allows to process 550 mm sheets at maximum. Die-cut and Kiss-cut in various substrates up to 0.3 mm or 0.013".




Rotary Die-Cutter RD-3346 + Separator SPC-3346



# RD series Features

## Die-Cutting Mechanism

The sheet passes between the upper die and the lower anvil roller to cut.




## Useful Function

### Repeat Function

Repeat register function enables the running of multiple up imposed applications with a smaller die to reduce die cost.

(RD-4055: Up to 5 repeats, RD-3346: Up to 8 repeats)




## Various Substrate

Rotary Die-cut System is suitable for various types of processing.


### Kiss Cutting

Die-cutting and Kiss cutting can be performed at the same time by using a die which has two different blade heights. Ideal for making stickers and labels.



### Creasing Only for RD-4055

Crease can be achieved to avoid image checking. Suitable for boxes, pocket folders and greeting cards which require an additional folding processes after die cutting.



# Details for Each Device



Sheet Feeder FFU-4055 + Rotary Die-Cutter RD-4055 + Separator SPC-4055

## 1 Operation Console

Both setup and control can be done through the intuitive touch screen. After setting upper and lower die, the system can be set up by simply inputting sheet size and product size. The graphical illustrations on the screen are simple and easy to understand.




## 3 Transport Section

Sheets are registered by vacuum belt and position is firmly secured with gripper rollers for high quality finish. Servo motor driven gripper rollers ensure the die cut position without effecting processing speed.



## 2 Feed Section

Vacuum belt feeding enables superior feeding with easy setup and operation. An ultrasonic sensor is used for double feed detection on a wide range of substrates.




## 4 Mark Sensor Option

The optional mark sensor reads the mark printed in the leading margin of sheet. If the printing image is offset, the position is automatically calibrated to process the sheet accurately.



## Sheet flow of Rotary Die-cut System



### 5 Die Cutting Section

Rigid magnetic upper roller and solid lower anvil roller ensure high quality die cutting. Uniquely designed die cutting section enables easy and quick die setting.



### 6 Separator Option

The connected separator removes the waste from the finished product and delivers it to the waste bin. Air cylinder driven separator pins and air jets can be used depending on size of the waste.



### Attaching the Lower Die

**\*Only for RD-4055**

For the RD-4055, the lower die can be attached to the lower anvil roller to make crease lines.



### 7 Delivery Section Supplied with the Separator

Finished products are delivered on the motorized conveyor. Intermittent conveyor movement maximizes the continuous operation in a small space. Gap can be adjusted depending on the size of the product for easy handling.





# Performance Enhancing Options

## ST-4055 Only for RD-4055

### Stacker

- ST-4055 stacks a wider range of substrates and applications such as thinner sheets or complicated shapes which can be difficult to separate.
- Vacuum belt transport ensures smooth delivery without separating die cut pieces.

- Offset stacking function is available by pre-set number.
- Maximum stack capacity: 170 mm or 6.69"


\* To connect the ST-4055, remove the SPC-4055.

### Vacuum Transport Section

The vacuum transport belt is decelerated before the stock reaches the backstop for accurate stacking without damage to the die-cut stock.


### Operation Console

ST-4055 can be set up by the touch screen at RD-4055. Icon based touchscreen ensures intuitive operation.



### Stack Section

Delivery tray slides out for easy removal of finished pile. Offset function is available for easy job handlings.



Prepare the compressor to meet the following specifications:

Specification for Compressor with ST-4055	
Rated Output of Prime Mover(Reference)	0.75 kW
Maximum Operating Pressure	0.8 MPa
Minimum Required Pressure	0.6 MPa or more
Minimum Discharge	85 Liters per minute
Type	Oil-free Type

## Other Options

Lower Die Tool Kit  
LDK-4055

This kit includes the necessary tools and materials to help for preparing the lower die efficiently.

Nick Punch  
RD-NP

This optional nick punch is a tool to makes nick on the die easily.



## BT-4055 Only for RD-4055

### Bucket Receiving Tray

- BT-4055 is bucket receiving tray to deliver none separated die cut sheet in on the receiving tray.

Prepare the compressor to meet the following specifications:

#### Specification for Compressor with BT-4055

Rated Output of Prime Mover(Reference):	0.2 kW
Maximum Operating Pressure	0.8 MPa
Minimum Required Pressure	0.6 MPa or more
Minimum Discharge	20 Liters per minute
Type	Oil-free Type



## ST-3346 Only for RD-3346

### Stacker

- Optional ST-3346 stacks a wider range of substrates and applications such as thinner sheets or complicated shapes which can be difficult to separate.
- Maximum stack capacity: 70 mm or 2.76"

\* Connect the ST-3346 in-line with the SPC-3346 separator.

Prepare the compressor to meet the following specifications:

#### Specification for Compressor with ST-3346

Rated Output of Prime Mover(Reference):	0.75 kW
Maximum Operating Pressure	0.8 MPa
Minimum Required Pressure	0.6 MPa or more
Minimum Discharge	85 Liters per minute
Type	Oil-free Type




# Specifications


## Machine Dimensions [Unit : mm / inch]

The available range of sheet size and sheet weight can be limited depending on the connected models. The production speed is affected by the combination of the models.


### Dimension of RD-4055




### Dimension of RD-3346





### Dimension of RD-4055+ST-4055





### Dimension of RD-4055+BT-4055




### Dimension of RD-3346+SPC-3346+ST-3346



Model	RD-4055			RD-3346		
Sheet Feeding System	Air Suction Feed Belt					
Sheet Size (Before processing)	 <b>Width x Length</b>	Max. 400 x 550 mm / 15.74" x 21.65" Min. 200 x 275 mm / 7.88" x 10.83"		Max. 330.2 x 550 mm / 13" x 21.65" *L400 to 460 mm /15.75" to 18.11": The production speed is reduced to half. *L460 to 550 mm or 18.11" to 21.65": Repeat die cutting only. Min. 170 x 275 mm / 6.69" x 10.83"		
Cut Product Size *The size may be limited depending on shape and sheet weight range.		With separator	Max. 376 x 530 mm / 14.8" x 20.8" Min. 50 x 80 mm / 1.97" x 3.15"	With separator	Max. 306 x 440 mm / 12.04" x 17.32" Min. 40 x 60 mm / 1.58" x 2.37"	
		Without separator (with nicks)	Max. 384 x 530 mm / 15.1" x 20.8" Min. Depending on die shape	Without separator (with nicks)	Max. 314 x 440 mm / 12.36" x 17.32" Min. Depending on die shape	
Processed Material	Normal paper, Coated paper, Cardboard					
Material Thickness	127.9 to 400 gsm Die Cutting : Max. 0.5 mm / 0.019" (In case of blade height: 0.8 mm / 0.031") 0.3 mm / 0.001" (In case of blade height: 0.6 mm / 0.023") Creasing : Max. 0.4 mm / 0.015" (In case of blade height: 0.8 mm / 0.031")			127.9 to 270 gsm Max. 0.3 mm / 0.011"		
Feeder Stack Height	500 mm / 19.68"			150 mm / 5.90"		
Die Size Upper Die	Max. 400 x 560 mm / 15.74" x 22.04" Min. 160 x 100 mm / 6.30" x 3.94"			Max. W330 x L460 mm / W12.99" x L18.11" Min. W160 x L70 mm / W6.30" x L2.76"		
Upper Cutting Blade Height	0.6 mm or 0.8 mm / 0.0236" or 0.0315"			0.6 mm / 0.0236"		
Production Speed	Die cut roller 6,000 cycles per hour (Please see below specification when ST-4055 is connected.)			Die cut roller 5,000 cycles per hour (If the sheet length is longer than 400 mm / 15.75", the number of processing sheet is limited to 2,500 sheets per hour. Please see below specification when ST-3346 is connected.)		
Voltage/Frequency	Single Phase 200 to 240 V, 50 / 60 Hz			Single Phase 200 to 240 V, 50 / 60 Hz, 4.5 A		
Machine Dimensions	With separator (FFU-4055+RD-4055+SPC-4055)	W3,584 x D820 x H1,195 mm / W141.2" x D32.3" x H47.1"		With separator	W2,739 x D695 x H1,105 mm / 107.9" x 27.4" x 43.5	
	Without separator (FFU-4055+RD-4055)	W2,510 x D820 x 1,195 mm / W98.9" x D32.3" x H47.1"		Without separator	W2,150 x D695 x H1,105 mm / 84.7" x 27.4" x 43.5	
Recommended Air Source	When the SPC-4055 / ST-4055 is used Rated Output of Prime Mover(Reference): 0.75 kW Maximum Operating Pressure: 0.8 MPa Minimum Required Pressure: 0.6 MPa or more Minimum Discharge: 85 Liters per minute Type: Oil-free Type  When the SPC-4055 is not used Rated Output of Prime Mover: 0.2 kW Maximum Operating Pressure: 0.8 MPa Minimum Required Pressure: 0.6 MPa or more Minimum Discharge: 20 Liters per minute Type: Oil-free Type			Rated Output of Prime Mover(Reference): 0.75 kW Maximum Operating Pressure: 0.8 MPa Minimum Required Pressure: 0.6 MPa or more Minimum Discharge: 85 Liters per minute Type: Oil-free Type		

ST-4055 Specifications		
Compatible Machines	RD-4055	
Sheet Size	 <b>Width x Length</b>	Max. 400 x 550 mm / 15.74" x 21.65" Min. 200 x 275 mm / 7.88" x 10.83"
Sheet Weight Range	Normal Paper, Coated Paper, Cardboard Material Thickness: Max. 0.5 mm or 0.02" 127.9 to 400 gsm	
Production Speed	Offset Stacking: 3,000 sheets per hour In the stacking speed reduction mode: 3,000 sheets per hour Straight Stacking without speed reduction mode: 6,000 sheets per hour (This production speed is limited according to the sheet thickness, sheet size, and the number of nicks.)	
Stack Capacity	Max. 170 mm / 6.69"	
Voltage/Frequency	Single Phase 200 to 240 V, 50 / 60 Hz	
Machine Dimensions	W1,490 x D830 x H1,030 mm / W58.7" x D32.7" x H40.6"	
Recommended Air Source	Mover (Reference): 0.75 kW Maximum Operating Pressure: 0.8 MPa Minimum Required Pressure: 0.6 MPa or more Minimum Discharge: 85 Liters per minute Type: Oil-free Type	

ST-3346 Specifications		
Compatible Machines	RD-3346	
Sheet Size	 <b>Width x Length</b>	Max. 330.2 x 550 mm / 13.00" x 21.65" Min. 170 x 275 mm / 6.69" x 10.83"
Sheet Weight Range	Normal Paper, Coated Paper, Cardboard Material Thickness: Max. 0.3 mm or 0.01" 127.9 to 270 gsm	
Production Speed	With speed reduction mode: 2,500 sheets per hour Without speed reduction mode: 5,000 sheets per hour (This production speed is limited according to the sheet thickness, sheet size, and the number of nicks.)	
Stack Capacity	Max. 70 mm / 2.75"	
Voltage/Frequency	Single Phase 200 to 240 V, 50 / 60 Hz	
Machine Dimensions	W760 x D645 x H890 mm / W30.0" x D25.4" x H35.0"	
Recommended Air Source	Mover (Reference): 0.75 kW Maximum Operating Pressure: 0.8 MPa Minimum Required Pressure: 0.6 MPa or more Minimum Discharge: 85 Liters per minute Type: Oil-free Type	

**The World Loves Books.**



\*The machine design and specifications are subject to change without any notice.

Distributed by

**HORIZON INTERNATIONAL, INC.**

510 Kuze Ooyabu-cho, Minami-ku, Kyoto, 601-8206, Japan Phone : +81-(0)75-934-6700, Fax : +81-(0)75-934-6708, [www.horizon.co.jp](http://www.horizon.co.jp)

160315/KM/RDseries/00E/TV